




LAGUNA

SMARTSHOP III 5x10

**16HP HSD ATC
LIQUID COOLED SPINDLE**

{MCNC SS3 5x10 HSD NO Drill Block}



SPECIFICATION:		DRAWN.S.B._4/7/2016_REV,1
POWER REQUIREMENTS.	480V, 60A, 3 PHASE	
FOOTPRINT.	110" W X 158" L	
WORKING AREA.	61" X 121"	
GANTRY CLEARANCE.	12"	
SPINDLE.	16HP LIQUID COOLED SPINDLE	
SPINDLE RPM.	3,000-24,000	
RAPID TRAVEL.	2000 IPM	
MAXIMUM CUTTING SPEED.	TOOLING AND MATERIAL DEFINED	
DUST PORT DIAMETER.	4"	
PRECISION HELICAL RACK & PINION. DRIVE SYSTEM FOR X AND Y AXES	30MM HEAVY DUTY LINEAR BEARING,ALL AXES	
CONTROLLER.	FANUC WITH DATA SERVER	
TOOL CONE	HSK	
SOLID STATE HOME SWITCH'S.	YES	
HEAVY DUTY WELDMENT TUBULAR STEEL FRAME.	5500 POUNDS	
CENTRALIZED LUBRICATION SYSTEM FOR ALL AXES.	YES	
VACUUM TABLE	6 ZONES	