


# LAGUNA

**{NEW}**

## SMARTSHOP II-2

5'x10' 12HP HSD SPINDLE



|   |   |   |
|---|---|---|
| SPECIFICATION:  |   | DRAWN,S.B._10/8/2019_REV,1              |
| POWER REQUIREMENTS.   | See Below,varies on vacuum choice.      |   |
| FOOTPRINT.  | 91" W X 151" L                          |   |
| WORKING AREA.   | 61" X 121"                              |   |
| GANTRY CLEARANCE.   | 10.5"                                   |   |
| SPINDLE.  | 12HP HSD ISO30 ATC ES951 SPINDLE        |   |
| SPINDLE RPM.  | 6,000-24,000                            |   |
| RAPID TRAVEL.   | 720 IPM                                 |   |
| MAXIMUM CUTTING SPEED.  | 550 IPM                                 |   |
| DUST PORT DIAMETER.   | 4"                                      |   |
| PRECISION HELICAL RACK & PINION.<br>DRIVE SYSTEM FOR X AND Y AXES | 25MM HEAVY DUTY LINEAR BEARING,ALL AXES |   |
| CONTROLLER.   | B+R PP65 STEPPER PACKAGE                |   |
|   |   |   |
| SOLID STATE HOME SWITCH'S.  | YES                                     |   |
| HEAVY DUTY WELDMENT TUBULAR<br>STEEL FRAME.                       | 3500 POUNDS                             |   |
| CENTRALIZED LUBRICATION SYSTEM<br>FOR ALL AXES.                   | YES                                     |   |
| VACUUM TABLE  | 6 ZONES                                 |   |
| VACUUM OPTIONS  | 2 vacuums for<br>5x10 table preferred.  | POWER REQUIRMENTS:                      |
| 2 pcs,10hp stock regen vacuum_3 phase                             |   | 220v,3 Phase,60 amps                    |
| 2 pcs,10hp stock regen vacuum_1 Phase                             |   | 220v,1 ph,80 amps_Requires 2 15hp VFD's |
| 2 pcs,8.6hp Becker vacuum_3 Phase                                 |   | 220v,3 Phase,70 amps                    |
|   |   |   |