



10HP VAC,2



10HP VAC,1



CUSTOMER
SUPPLIED
WIRING.

151"

66"

SMARTSHOP M

CONTROL
CABINET

25"

24"

78"

SMARTSHOP M

57"

66"

91"

LAGUNA

{New}

SMART SHOP M2 5' X 10'
2PCS 10HP VACUUMS

SPECIFICATION:

DRAWN,S.B._10/3/2019_REV,4

POWER REQUIREMENTS. (See Note:)	220V,60A,3 PH. OR 80A,1PH. W/ VAC.VFDS
FOOTPRINT.	91" W X 151" L X 78" TALL
WORKING AREA.	61" X 121"
GANTRY CLEARANCE.	10.5"
SPINDLE.	5.5hp,HETICO Spindle,ISO30
SPINDLE RPM.	6,000-24,000
RAPID TRAVEL.	600 IPM
MAXIMUM CUTTING SPEED.	350 IPM
DUST PORT DIAMETER.	4"
PRECISION HELICAL RACK & PINION. DRIVE SYSTEM FOR X AND Y AXES	25MM HEAVY DUTY LINEAR BEARING,ALL AXES
CONTROLLER.	LAGUNA HAND HELD ATC CONTROLLER
TABLE TOP MATERIAL	PVC, POD READY TABLE
SOLID STATE HOME SWITCH'S.	YES
HEAVY DUTY WELDMENT TUBULAR STEEL FRAME.	2500 POUNDS
CENTRALIZED LUBRICATION SYSTEM FOR ALL AXES.	YES
VACUUM TABLE	4 ZONES
VACUUM PUMP OPTIONS	{10HP,3PH,REGEN VACUUM} OR {5.4HP 3PH BECKER VANE PUMP}

Notes on Power requirements: VFD's are used for 3 phase vacuums when single phase is used to power machine.
Specifications are subject to change without notice.