Scan For More Info

C|FLUX I





Scan For More Info

C|FLUX III

CIFI_UX: SPECIFICATIONS

Part Number:	MDCCF15110
Motor:	1½HP, 110V, 1PH, 60Hz
Full Load Amperage:	18.8 Amps (110V)
6ft. 3 Wire Cord with No Plug:	√
RPM:	3450
Switch:	Magnetic On/Off
Hand-held Remote Control:	High Frequency
Inlet CFM:	1314 CFM
Shop Setting CFM:	900 CFM
Max Static Pressure (inches of water):	10.1"
Inlet Diameter:	6"
Inlet Splitter:	2" x 4" Ports
Impeller:	13.5" Steel Radial Fin
Drum Capacity:	32 Gal.
Bag Hold-Down:	Metal Insert
Canister Filter Type:	1 Micron
Filtration Efficiency:	0.2-2 micron @ 99.97%
MERV Rating:	12
Canister Cleaning:	Manual Crank 360°
Decibel Reading:	82 dBA (@9.8ft)
Dimensions:	43" x 24" x 69"
Weight (Net/Ship):	232/287 Lbs.

*220V Operation requires purchase of additional parts.

CIFI_UX: E SPECIFICATIONS

Part Number:	MDCCF32201
Motor:	3HP, 220V, 1PH, 60Hz, 22 Amps
Recommended Breaker Size:	30 Amps
6ft. 3-Wire Cord with No Plug:	\checkmark
RPM:	3450
Switch:	Magnetic On/Off
Hand-held Remote Control:	High Frequency
Inlet CFM:	2817 CFM
Shop Setting CFM:	1624 CFM
Max Static Pressure (inches of wate	er): 11.2"
Inlet Diameter:	8"
Inlet Splitter:	3" x 4" Ports
Impeller:	15.5" Steel Radial Fin
Drum Capacity:	46 Gal.
Bag Hold-Down:	Metal Insert
Canister Filter Type:	1 Micron
Filtration Efficiency:	0.2-2 micron @ 99.97%
MERV Rating:	12
Canister Cleaning:	Manual Crank 270°
Decibel Reading:	88 dBA (@9.8ft)
Dimensions:	48" x 28" x 89"
Weight (Net/Ship):	309/375 Lbs.

CIIFI_UX: 1, 2 & 3

CIFI_UXE SPECIFICATIONS

Part Number: Motor: Recommended Breaker Size: 6ft. 3-Wire Cord with No Plug: RPM: Switch: Hand-held Remote Control: Inlet CFM: Shop Setting CFM: Max Static Pressure (inches of water): Inlet Diameter: Inlet Splitter: Impeller: Drum Capacity: Bag Hold-Down: Canister Filter Type: Filtration Efficiency: **MERV** Rating: **Canister Cleaning:** Decibel Reading: Dimensions: Weight (Net/Ship):

MDCCF22201 2HP, 220V, 1PH, 60Hz, 14 Amps 20 Amps \checkmark 3450 Magnetic On/Off **High Frequency** 1740 CFM 1166 CFM 9.3" 8″ 2" x 4" Ports 14.5" Steel Radial Fin 46 Gal. Metal Insert 1 Micron 0.2-2 micron @ 99.97% 12 Manual Crank 270° 88 d B(A) (@9.8ft) 48" x 28" x 89" 301/377 Lbs.

C|FLUX ACCESSORIES

REUSEABLE HEAVY DUTY PLASTIC BAGS

ADBAG22CP123X5 PDCCF-FB22 5-Pack Collection Drum Bags 5-Pack Canister Filter Bags





CIFILUX: 1, 2 & 3 SECRETS

Scan For More Info







CIFLUX I

C|FLUX II

CIFLUX III



THE GOLDEN TRIANGLE

Laguna has made dust collection easy for users with our line of feature-rich cyclone dust collectors. We have optimized the position and angle of inlet, the diameter of the barrel, the shape of the cyclone cone, along with other details which must all work together.




HF REMOTE

2

Laguna has designed the remote for the AIR category to operate using high frequency. This technology does not require line-of-sight and will not interfere with fluorescent lights

9



One Piece Main Plenum Allows Direct Airflow Helps reduce resistance

Radial Steel Fan -3 Balanced to ISO 1940 Standards



5

2

Splitter Inlet & Sealed Cap Made of Rubber, not hard plastic

*C|Flux 2&3 - Metal Inlet Splitter

Filter Surface Area Up To 120% Larger Than Competitors Canister Paper Made in Denmark

6

Ingenious Lift System Eliminates Flex Hose Patented lift design creates strong seal



6

High Quality Swiveling Casters 4" Diameter (2 Locking for Main Base)

3" Diameter Drum Casters

Newly Designed Dual Paddles Provides twice the cleaning



8

Filter Cleaning Handle