P||F||U||X: 1, 2 & 3

Peerless performance. Featuring standard black HEPA filtration, the P|Flux series is filled with innovative details such as:

- ·LED and alarm when drum is full
- Automatic Filter Cleaning
- LED Drum illumination
- Swing away doors with acoustic foam on inside to lower noise level.

P F L UX SPECIFICATIONS

MDCPF15110 Part Number: Motor: 1-1/2HP, 110V, 1PH, 60Hz, 18.8 Amps Recommended Breaker Size: 25 Amps 6ft. 3-Wire Cord with No Plug: RPM: 3450 Control Panel: **Anodized Aluminum** Switch: Magnetic On/Off Hand-held Remote Control: High Frequency Automatic Clear Filtering:

Drum Full Warning: LED + Alarm Inlet CFM: 1314 CFM
Shop Setting CFM: 900 CFM

Max Static Pressure (inches of water): 10.1"
Inlet Diameters: 6"

Inlet Splitter: 2" x 4" Ports Impeller: 13.5" Steel Radial Fin

Drum Capacity: 25 Gallon

Bag Hold-Down: Metal Insert
Canister Filter Type: HEPA

Filtration Efficiency: 99.7% of particles 0.3 + larger

MERV Rating: 16+

Canister Cleaning: Automatic Filter Cleaning
Decibel Reading: 70 dBA (@9.8ft)

Assembled Dimensions: 42" x 25" x 68" LxWxH Weight (Net/Ship): 232/287 Lbs.







PIFLUX I PIFLUX II

PIFLUX III



Part Number: MDCPF22201 Motor: 2HP, 220V, 1PH, 60Hz, 14 Amps Recommended Breaker Size: 20 Amps 6ft. 3-Wire Cord with No Plug: RPM: 3450 Control Panel: **Anodized Aluminum** Switch: Magnetic On/Off Hand-held Remote Control: High Frequency Automatic Clear Filtering: Drum Full Warning: LED + Alarm Inlet CFM: 1740 CFM 1166 CFM Shop Setting CFM: Max Static Pressure (inches of water): 9.3" Inlet Diameters: 8" 2" x 4" Ports Inlet Splitter: Impeller: 14.5" Steel Radial Fin Drum Capacity: 46 Gallon Bag Hold-Down: Metal Insert **HEPA** Canister Filter Type: Filtration Efficiency: 99.7% of particles 0.3 + larger MERV Rating: Canister Cleaning: **Automatic Filter Cleaning**

76 dBA (@9.8ft)

362/430 Lbs.

48" x 28" x 88" LxWxH

Decibel Reading:

Weight (Net/Ship):

Assembled Dimensions:



PITLUX: SPECIFICATIONS

Part Number:

MDCPF32201

Inlet CFM: Shop Setting CFM: 2817 CFM

Motor:

3HP, 220V, 1PH, 60Hz, 22 Amps Max Static Pressure (in. of water):

1624 CFM

Recommended Breaker Size: 6ft. 3-Wire Cord with No Plug: 30 Amps Inlet Diameters:

11.2" 8"

RPM:

√ Inlet Splitter:

2" x 4" Ports

Control Panel:

3450 Impeller:

15.5" Steel Radial Fin

Switch:

Anodized Aluminum Drum Capacity:

High Frequency Canister Filter Type:

82 dBA (@9.8ft) Weight (Net/Ship):

46 Gallon

Magnetic On/Off Bag Hold-Down:

Metal Insert

Hand-held Remote Control:

√ Filtration Efficiency:

HEPA 99.7% of particles 0.3 +

Automatic Filter Cleaning **Drum Full Warning**

LED + Alarm MERV Rating:

larger 16+

ANDAIRCON Canister Cleaning: Decibel Reading:

Automatic Filter Cleaning Assembled Dimensions:

48" x 28" x 88" LxWxH

372/441 Lbs.



HEPA Filter w. **Automatic Cleaning**



RF Remote w. On/Off + Manual Filter Cleaning



Centralized Control Panel Can be Mounted on Left/Right Side



Drum Quick Release Pulls Drum Firmly Against Lid

LUX ACCESSORIES

REUSEABLE HEAVY DUTY PLASTIC BAGS

ADBAG22CP123X5 PDCCF-FB22

5-Pack Collection Drum Bags 5-Pack Canister Filter Bags



P|FLUX I



P|FLUX III



